



- H.265X 1080P 2.0 Mega Pixels Pan/Tilt WIFI IP Camera
- HD 3.6mm IR Distance 10-20m
- Support ONVIF with net cable
- Support computer client remote / local viewing
- Motion Track Could Pan 355 Degree , Tilt 90 Degree
- Support dual-stream, support 2.4GHz WIFI wifi distance 100 meters
- Support TF Card for local storage (Max.128GB);Free one month cloud storage.
- Support multiple mobile monitoring (iOS, Android) Mobile APP : ICSEE (5 users remote viewing simultaneously)
- Support automatic color to black function, realize day to night monitoring
- Support automatic electric shutter function, adapt to different monitor environments.
- Support Motion Alarm (Humanoid detection switch, Show Traces, Perimeter Alert, Cordon, Alert Area)
- Support Two-ways Audio intercom
- 5DB three antenna wireless camera
- Add mode : QR code / network cable / AP hotspot;
- 1 RJ45 Interface, 10/100M self-adaption and reset button
- Plug and play, multiple network cloud services open security cloud monitoring
- Support Alarm Action (Snapshot , Take a Video, Device Beep)

Model		YSR-A1
Camera Features	Image sensor	2.0M 1/2.7" f37 CMOS sensor
	Video compression	H.265X coding,support dual stream,AVI;0.1M~8Mbps variable
	Image output	Main stream: 1920*1080@25fps; sub-stream: 640*360@25fps
	Min. Illumination	Color: 1.5 Lux; W/B: 0 Lux with IR LED ON
	Shutter	1/50(1/60) seconds to 1/100,000 seconds
	Focus Length	HD 3.6mm @F1.8 (6mm Optional)
	Lens Mode	Fixed lens
	Infrared LED	6 PCS
	Infrared Distance	10-20m
	Day/Night	Color/ B&W (IR-CUT)
Interface	Motion Detection	Support
	Video Output	Network
	TF card	Support external 128 GB Micro TF card
	Audio I/O	Support two-way Audio
	Automatic tracking	YES
	Double light	—
	Wifi	WiFi 802.11b/g/n wireless network
General	Material	ABS plastic Non-water proof
	ONVIF	Support ONVIF 2.4 with cable
	Pan/Tilt Angle	Horizontal:355° & Vertical:90°
	Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
	IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari
	Operation Temperature	-10°C- + 60°C
	Storage Temperature	10%-90% RH
	Power Supply	DC5V±10%
	Consumption	MAX 5 W
	Dimensions	L155*W122*H222 mm
	Weight	About 300g